

Applicant: Gerhard GROSS et al  
Docket No. R.308338  
Preliminary Amdt.

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claims 1-5. (Canceled)

6. **(New)** In a sintered slide bearing for a shaft of an electrical machine which bearing has a bore for the shaft and also has capillary gaps and is saturated with a lubricant, the improvement wherein at least the surface region of the bore has zones of different density, which are saturated with a low-viscosity poly-alpha-olefin lubricant.

7. **(New)** The slide bearing as defined by claim 6, wherein the viscosity at 40°C is 22 mm<sup>2</sup>/s and at 100°C is 4.8 mm<sup>2</sup>/s.

8. **(New)** The slide bearing as defined by claim 6, wherein the ratio of the length to the width of the capillary gaps is between 2.5/0.75 and 1.4/0.8.

9. **(New)** The slide bearing as defined by claim 7, wherein the ratio of the length to the width of the capillary gaps is between 2.5/0.75 and 1.4/0.8.

Applicant: Gerhard GROSS et al  
Docket No. R.308338  
Preliminary Amdt.

10. **(New)** The slide bearing as defined by claim 6, wherein the ratio of the length to the width of the capillary gaps is between 2/0.9 and 1.4/0.45.
11. **(New)** The slide bearing as defined by claim 7, wherein the ratio of the length to the width of the capillary gaps is between 2/0.9 and 1.4/0.45.
12. **(New)** An electrical machine having at least one bearing as defined by claim 6.
13. **(New)** An electrical machine having at least one bearing as defined by claim 7.
14. **(New)** An electrical machine having at least one bearing as defined by claim 8.
15. **(New)** An electrical machine having at least one bearing as defined by claim 10.